
## DiaMassive-25H

Drainage board for surfaces exposed to high loads

## **ADVANTAGES**

- Extremely high compressive strength ⇒ can be used by heavy vehicles
- Can be paved frost-free
- Stable form
- Economical installation ⇒ negligible overlap loss
- Enviroment protection ⇒ made from recycled primary waste which can be recycled



DIADEM<sup>®</sup> BUILD-UP

Concrete tiles Sand bedding VLF-150 / VLF-200 filter geotextile Grit bedding (4 mm – 11 mm) **DiaMassive-25H** VLU-300 / VLU-500 protection fleece GF-1000 skid layer (2 layers) VLU-300 / VLU-500 protection fleece Root-resistant layer Existing build-up (roof deck)



## APPLICATION

Rainwater retention and drainage plate extensive and semi-intensive green roofs and paved surfaces subject to vehicular traffic, made of recycled polystyrene with increased impact resistance (HIPS). The specially designed barrier structure provides a run-off retarding effect.

## SPECIFICATION

Heavy duty flow-delay drainage board of recycled high-impact polystyrene, 25 mm high, of paved/wooden surfaces of roof areas and for gravel roof build-up. Due to its excellent load bearing capacity it is appropriate for drainage layer under heavy vehicle roads. Compressive strength 1089,2 kN / m<sup>2</sup> (unfilled), water flow capacity on 2% roof slope 0,57 l / m<sup>x</sup>s certified according to EN ISO 12958.

Product: DIADEM<sup>\*</sup> DiaMassive-25H Producer's certificate: A.P.P. Kft. Website: www.diadem.com





Microbiological resistance EN 12225



TECHNICAL DATA	
Board size (cm):	202 × 110 × 2,5
Overlap loss:	< 4%
Fill-up volume (l / m²):	13,5
Weight (kg / m²):	2,25
Compressive strength filled (kN / m <sup>2</sup> ):	1839,6
Compressive strength unfilled (kN / m <sup>2</sup> ):	1089,2
Material:	HIPS
Water flow capacity EN ISO 12958 (I / m×s):	at 1%: 0,39 • at 2%: 0,57 • at 3%: 0,71 • at 5%: 0,91
Storage:	horizontally, for long-term storage protect from UV radiation
Installation:	adjacent to each other or overlapped



DIADEM® A.P.P. Kft., H–9028 Győr, Fehérvári út 75. Tel.: +36 96 512 910 • info@diadem.com • www.diadem.com APP Dachgarten GmbH, D–85049 Ingolstadt, Jurastrasse 21. Tel.:+49 841 370 9496 • info@diadem.com • www.grundach.com DIADEM CH AG. CH-4710 Balsthal, Rauracherweg 1. Tel.: +41 79 328 37 74 • info@diadem.com • www.diadem.ch



Green Up the Roof!